



DISCOVER THE POWER OF THE **GEOTHERM LOGIC 5.5** WITH BORE LOGIC



Please call me with any questions, we would appreciate the opportunity to provide you with your equipment & service needs!



(317) 695-0728



jim.hopkins@borelogic.com

www.borelogic.com

**SAFETY
FOCUSED**

**PERFORMANCE
DRIVEN**

**RELIABILITY
PROVEN**



www.borelogic.com

DISCOVER THE POWER OF THE GTL5.5 WITH BORE LOGIC

SIZE AND WEIGHT

- **Transport Dimensions (LxBxH):**
14.65 ft × 6.73 ft × 8.56 ft
- **Weight:**
13,228 lbs.
- **Undercircuit type / Pad width:**
VTS 7000 | 15.75 in.

POWER UNIT

- **Engine:**
Kubota V2403-CR-TE5B
48,6kW@2700rpm | Stage V | Diesel.

CAPACITY

- **Fuel tank capacity:**
26.4 gal
- **Oil tank capacity:**
26.4 gal
- **Hopper capacity:**
475 gal | 5500 lbs
- **Mixer, holding capacity / mix preparation capacity:**
2 x 92 gal | 22 GPM
- **Water buffertank capacity:**
2 x 47 gal
- **Injection pump capacity (pistonpump):**
22 GPM @ 362 psi
- **Grouting hosereel capacity:**
984 ft | 1.57 in
- **Hosereel capacity geothermal probes:**
Dia.5.25 ft | Width: 2.75 ft
Dia int.:2.2 ft -> 2.85 ft
- **Danfoss Load-sensing pump capacity:**
42 gpm @ 3263 psi



Your entire looping and grouting operation mounted on a track crawler. Twin mixers, an integrated super sack hopper, automated mix-and-pump controls, and a powered geo loop loader work together seamlessly, eliminating the equipment shuffle and keeping crews productive from setup to shutdown.

SAFETY FOCUSED

PERFORMANCE DRIVEN

RELIABILITY PROVEN



OPTIONAL

- **Loader crane:**
Range 11.7 ft | Capacity 25,800 ft-lb (2205 lbs @ 11.7 ft)
- **Power generator:**
5.2-6.5 kW | 240V | 50Hz
- **Power washer / hose reel (length):**
2176 PSI | 5.28 gpm | 2176 psi | .53 gpm | 49 ft"
- **Water pump test cycle capacity / tankvolume:**
Leo-Pump 1320 gal | 72 psi | 26 gal
- **Pentair pump (self priming) drilling water:**
Hypro/Pentair-pump 26.4 GPM | 79 psi

